

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

1. (canceled)
2. (canceled)
3. (canceled)
4. (canceled)
5. (canceled)
6. (canceled)
7. (canceled)
8. (canceled)
9. (canceled)
10. (canceled)
11. (canceled)
12. (canceled)
13. (canceled)
14. (canceled)
15. (canceled)
16. (new) An acoustic contact detecting device, comprising:
 - (a) a substrate having a top surface;
 - (b) an acoustic wave transducer for coupling with a first wave representative of a bulk wave being propagated through said substrate along an axis crossing said top surface;
 - (c) a planar wiring for supplying said acoustic wave transducer with electric power printed on the substrate;
 - (d) a diffractive acoustic wave mode coupler having a mode of converted wave having high energy on said top surface and functioning for coupling a second wave being propagated along an axis parallel to said top surface with said first wave; and
 - (e) a means for detecting a perturbation in energy of said second wave.
17. (new) A coordinate input device of touch type comprising: a propagation medium having a top surface capable of propagating an acoustic wave; a bulk wave generation means for propagating a bulk wave in a crossing direction with respect to said top surface of said propagation medium; a planar wiring for supplying said bulk wave generation means with electric power printed on the propagation medium; an acoustic wave generation means for converting said bulk wave into an acoustic wave and propagating said acoustic wave on the

top surface of said propagation medium; and a detecting means for detecting a scatter in the surface of the acoustic wave from said acoustic wave generation means.

18. (new) A device in accordance with claim 16, in which said acoustic wave transducer is composed of a piezoelectric vibrator.

19. (new) A device in accordance with claim 16, in which said wiring is formed by using conductive paste.

20. (new) A device in accordance with claim 16, in which said wiring is formed by way of transfer printing.

21. (new) A device in accordance with claim 16, in which said wiring is formed on a back surface of the substrate.

22. (new) A substrate for an acoustic detecting device having a top surface, said substrate further comprising:

- (a) an acoustic wave transducer coupled with a bulk wave having a propagation axis crossing said top surface in said substrate;
- (b) a wiring for supplying said acoustic wave transducer with electric power, said wiring being printed on a back surface of said substrate;
- (c) a diffractive acoustic wave mode coupling structure formed in the proximity to said surface for converting acoustic energy of the bulk wave into a wave to be propagated along an axis parallel to said top surface; and
- (d) a means for detecting the converted acoustic wave energy corresponding to a position of a perturbation event.

23. (new) A touch input device, comprising:

- (a) a substrate having a first planar surface and a second planar surface;
- (b) an acoustic wave transducer for generating acoustic waves, the acoustic wave transducer coupled to the second planar surface such that generated acoustic waves are transmitted to the first planar surface;
- (c) planar wiring printed on the second planar surface; and
- (d) means for connecting the planar wiring to the acoustic wave transducer.

24. (new) A touch input device as recited in Claim 23, wherein the means for connecting the planar wiring to the acoustic wave transducer comprises a first electrode that couples a first

portion of a first side of the transducer to a first portion of the planar wiring and a second electrode that couples a second portion of the first side of the transducer to a second portion of the planar wiring wherein the second electrode extends from the first side of the transducer to a second side of the transducer opposed to the first portion of the first side of the transducer.

25. (new) A touch input device as recited in Claim 24, wherein the first portion of the planar wiring is insulated from the second portion of the planar wiring.

26. (new) A touch input device as recited in Claim 23, wherein the planar wiring comprises a composite conductive material.

27. (new) A touch input device as recited in Claim 23, wherein the planar wiring is applied by transfer printing.

28. (new) A touch input device as recited in Claim 23, further comprising a linear array of acoustically reflective elements on the first planar surface and wherein the planar wiring resides on a portion of the second planar surface substantially opposite to the linear array of acoustically reflective elements.

29. (new) A device in accordance with claim 17, in which said acoustic wave transducer is composed of a piezoelectric vibrator.

30. (new) A device in accordance with claim 17, in which said wiring is formed by using conductive paste.

31. (new) A device in accordance with claim 17, in which said wiring is formed by way of transfer printing.

32. (new) A device in accordance with claim 19, in which said wiring is formed by way of transfer printing.

33. (new) A device in accordance with claim 30, in which said wiring is formed by way of transfer printing.

34. (new) A device in accordance with claim 17, in which said wiring is formed on a back surface of the substrate.